BOOST YOUR BUSINESS PRODUCTIVITY WITH FAST AND EFFICIENT MULTI-FUNCTIONAL BLACK AND WHITE LASER PRINTERS



i-SENSYS MF450 series

Designed for small to medium businesses or individuals working remotely, the Canon i-SENSYS MF450 Series is compact, efficient, and productive.







MOBILE PRINTING





Cloud connectivity

Print or scan from the cloud, with one -touch built-in connectivity to cloud storage services, including Google Drive, DropBox, and OneDrive.

Mobile printing

Conveniently print documents from your from smartphone or tablet with the Canon PRINT Business app, or via AirPrint (iOS) and Mopria (Android).

Reliable security

Protect your documents with Secure PIN functionality, which restricts printing of sensitive documents, and avoid hacking or virus threats with Verify System at Startup.

Superior efficiency

Super-fast print speeds, double-sided single-pass scanning and double-sided printing as standard ensure ultimate productivity.

Customised workflows

Automate everyday tasks such as printing stored forms, scanning to email, and copying documents with on-screen buttons and Canon's Application Library.



RANGE FEATURE STEP UP CHART





MF453dw

MF455dw

Fax		•
A4 print speed	38ppm	38ppm
Display	12.7cm colour touch screen	12.7cm colour touch screen
Secure PIN print	•	•
Duplex printing	•	•
Built-in cloud connectivity	•	•
Application Library	•	•
Single Pass Duplex Scan	•	•
Wireless connectivity	•	•



TECHNICAL SPECIFICATIONS

i-SENSYS MF450 series

Available functions

MF455dw: Print, Copy, Scan and Fax MF453dw: Print, Copy and Scan

PRINTER

Print speed

Printing method Warm-up time

First Print Out Time Printer languages

Print margins

Fonts

Toner saver mode Advanced printing features

COPIER

Copy speed First Copy Output Time (FCOT)

Copy resolution Copy modes

Double sided copying Multiple copy

Reduction / Enlargement

Other features

SCANNED Туре

Scan resolution Scan speed

Colour scanning depth Greyscales Compatibility Max. scan width Scan to E-mail

Scan to PC Scan to USB memory key Scan to FTP

Scan to Cloud iFΔX

FAX

Modem speed Receive mode Fax resolution

FAX memory

Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing

Other features MEDIA HANDLING

Scanner type Paper input (Standard)

Paper input (Option)

Paper output Media types

Media sizes

Mono Laser All-In-One

Single sided : Up to 38 ppm (A4) Up to 63.1 ppm(A5-Landscape) Double sided : Up to 31.9 ipm (A4)

Monochrome laser beam printing

Up to 1200 x 1200 dpi

Approx. 14 seconds or less from power on

Approx: 5.5 seconds or less

UFRII, PCL 5e², PCL6, Adobe* PostScript³

45 PCL fonts 136 PostScript fonts

5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)

Yes

Secure Print
Print from USB memory key (JPEG/TIFF/PDF)
Print from Cloud' (Dropbox, GoogleDrive, OneDrive) (PDF/JPEG)
iOS: AirPrint, Canon PRINT Business app
Android; Mopria certified, Canon PRINT Business app, Canon Print
Service Plug-in

Single sided (A4): Up to 38 ppm Double sided (A4): Up to 30.3 ipm ADF (A4): Approx. 6.6 seconds or less Platen (A4): Approx. 6.4 seconds or less

Up to 600 x 600 dpi

Text, Text/Photo (Default), Text/Photo (High Quality), Photo

2-sided to 2-sided (Automatic)

Up to 999 copies

25-400% in 1% increments

Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy

Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi

Single sided mono: 38ipm (300x600dpi) Single sided colour: 13ipm (300x600dpi) Double sided mono: 70ipm (300x600dpi) Double sided colour: 26ipm (300x600dpi)

24 bit/24 bit (input/output)

256 levels

TIFF/JPEG/PDF/Compact PDF/Searchable PDF

TIFF/JPEG/PDF/PNG3

ITU-T.37

MF455dw ONLY

33.6 Kbps (Up to 3 seconds/page⁴)

Fax only, Fax/Tel Auto Switch, Answer Mode, Manual

Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi Up to 512 pages4 Up to 281 dials

Max. 299 dials / Max. 299 destinations

Max. 310 destinations

Permanent fax memory backup (Backup with flash memory)

Yes (Transmit and Receive)

Sender's Name (TTI), Direct Send, TX Report, Sequential

Broadcasting

Platen, 2-sided ADF (single pass) 250-sheet cassette 100-sheet multi-purpose tray 50-sheet ADF

550-sheet cassette

150-sheet

Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post

Cassette (Standard and optional): Cassacte (Standard and Opinion).

A4, A5, A5 (Clandscape), A6, B5, Legal, Letter, Executive, Statement,
OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K,
Custom sizes: Min. 105 x 148 mm Max. 216.0 x 355.6 mm.

Multi-purpose tray:
A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement,
OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K,
Indexcard, Envelope (COM10, Monarch, C5, DL), Custom sizes: Min
76.2 x 127 mm Max. 216.0 x 355.6 mm.

ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 105 x 128 mm Max 215.9 x 355.6 mm

Media weights

Interface type

Operating System compatibility

Network Protocol

Double sided printing

INTERFACE & SOFTWARE

Cassette (standard and optional): 60 to 120 g/m² Multi-purpose tray: 60 to 163 g/m² ADF: 50 to 105 g/m²

A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscap Custom size - Min. 210 x 279.4 mm Max. 216.0 x 355.6 mm 60 to 120 g/m²

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Windows* 11 / Windows* 10 / Windows* 8.1 / Server* 2019 / Server* 2016 / Server* 2012R2 / Server* 2018R2 / Server* 2008R2 / Server* 2008 Mac OS X version 10.11 & up Linux⁵

Print: TCP/IP (LPD/Port9100/IPP/IPPS/WSD)

Push Scan: File: FTP (TCP/IP), SMB3.0 (TCP/IP) E-mail/I-Fax: SMTP (send), POP3 (receive) Pull Scan: TCP/IP

Management: SNMPv1, SNMPv3 (IPv4,IPv6)

Security: TLS1.3, IPSec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS)

Security (wireless): Infrastructure Mode: WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES)

Access Point Mode: WPA2-PSK(AES)

Software and printer management

WPAZ-PSK(AES)
MF Scan Utility,
Remote User Interface (RUI),
Department ID Management,
Toner Status Tool,
IW Enterprise Management Console: Server-based software for
centralised management of a fleet of devices
eMaintenance: embedded RDS allows remote eMaintenance
services such as meter capture, automatic kvanto.com.ua consum
management and remote diagnostics
Application Library ua consumables

800MHz x 2

Approx. 17.2 Kg

1GB

750 - 4,000 pages per month

Max, 80,000 pages per month⁶

12.7 cm LCD Colour Touch Screen

453 mm x 464 mm x 392 mm

682 mm x 1.083 mm x 895 mm

GENERAL FEATURES

Recommended Monthly Print Volume

Duty cycle Processor Speed Memory

Control panel Dimensions with trays (W x D x H)

Installation space (W x D x H)

Weight Operating environment

Power Source

Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240V(±10%) 50/60Hz (±2Hz)

Power Consumption

Maximum: Approx. 1,370 W Standby: Approx. 9.4 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 0.33 kWh/week

(230V) ¹¹ For detailed information relating to Lot26 regulation, please

go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx

Sound Pressure⁷ Active: 53 dB Standby: Inaudible⁸ Sound Power Active: 72.2 dB

Standby: Inaudible⁸

CONSUMABLES

Noise Levels

Cartridges

Cartridge 057 (3,100 pages ⁹)¹⁰ Cartridge 057H (10,000 pages ⁹)¹⁰

ACCESSORIES/ OPTIONS

Items

MF455dw: CST.Feeding Module-AH1 (550-sheet cassette) TEL 6 Kit Long Cord (Telephone handset) MF453dw:

CST.Feeding Module-AH1 (550-sheet cassette)

Notes:

Subscription to a third party cloud service is required, and subject to their party terms and conditions.

A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

Scan by MF Scan Utility or Canon PRINT Business

[4] Based on ITU-T Standard Chart No. 1

Linux support both printing and scanning

Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

Declared noise emission in accordance with ISO 9296

Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779

[9] Based on ISO/IEC 19752

[10] Printer ships with Cartridge 057 (3,100 pages)

[11] As per US ENERGY STAR* version 3.0.





PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS MF453dw	5161C007BA	4549292186512
i-SENSYS MF455dw	5161C006BA	4549292186505

ACCESSORIES:

PRODUCT NAME	Mercury Code	EAN Code
Cassette Feeding Module-AH1	0732A033AA	4549292092769
Telephone 6 Kit EU (CW)	0752A054AA	4960999453910
Telephone 6 Kit UK (CW)	0752A053AA	4960999453897
Telephone 6 Kit SA (CW)	0752A055AA	4960999453927

CONSUMABLES:

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 057	3009C002AA	4549292136258
Cartridge 057 H	3010C002AA	4549292136289

Canon Inc. canon.com

Canon Europe canon-europe.com

